



BRX Elite Eurosyn Motor Oil

Bel-Ray® BRX Elite Eurosyn Motor Oil is formulated exclusively with premium synthetic base stocks and advanced additive technology to deliver trusted engine protection and peak vehicle performance. Bel-Ray® BRX Elite Eurosyn provides aggressive resistance to sludge formulation and varnish deposits during stop-and-go driving under severe operating conditions. Premium synthetic formulation delivers excellent oxidation stability and low volatility properties, resulting in reduced oil consumption between services. Recommended for service in European gasoline and light-duty diesel applications including naturally aspirated and turbo-charged engines, direct injection gasoline engines, and turbocharged direct injection diesel engines found in passenger cars, light-trucks, and sport utility vehicles.

APPLICATIONS

- Licensed under API SN standard; backward compatible with all prior API standards
- ACEA A3/B3-12 & A3/B4-12
- Mercedes Benz 226.5, 229.3 & 229.5
- Opel GM-LL-B-025
- Porsche A40
- PSA B712296
- Renault RN0700 & RN0710
- Volkswagen 502.00 & 505.00

PRODUCT FEATURES

- Exceeds API SN and ACEA A3/B4-12, A5/B5-12 performance standards
- Formulated exclusively with select synthetic base stocks for maximum resistance to thermal breakdown
- Excellent oxidation stability and volatility properties reduce oil consumption between services
- Advanced additive technology provides added resistance to sludge formation and piston deposits
- Meets European OEM engine oil specification performance requirements

BENEFITS

- Excellent wear protection to protect critical engine components
- Optimum fuel economy
- Excellent low-temperature performance for cold starts
- Long-lasting protection of vehicle emission systems
- Excellent oxidation stability supports extended service intervals

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

10/26/2021



| Typical Physical Properties | | |
|-----------------------------|-------------|--------------|
| Property | Test Method | 5W-40 |
| API Service | | SN |
| Density@15°C, g/cm3 | ASTM D4052 | 0.852 |
| Viscosity @ 40°C, cSt | ASTM D445 | 82.8 |
| Viscosity @ 100°C, cSt | ASTM D445 | 13.7 |
| Viscosity Index | ASTM D2270 | 170 |
| Flash Point, °C (°F) | ASTM D92 | 221 (430) |
| Pour Point, °C (°F) | ASTM D97 | -48 (-54) |
| Cold Crank Simulator, cP | ASTM D5293 | 5,871 @-30°C |
| TBN, mg KOH | ASTM D2896 | 5.1 |

DISTRIBUTED BY:
Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

10/26/2021