

Electric Switch Contact Black Grease

Electric Switch Contact Black Grease, commonly known as Bel-Ray 64982 Grease, is a mineral oil in non-melting gel system with a combination of moly and PTFE. The exceptional low frictional properties and load carrying abilities of Electric Switch Contact Black Grease are derived from its unique combination of moly and PTFE. Electric Switch Contact Black Grease delivers exceptional performance on sliding surfaces and thread applications. Effective over a broad temperature range for the most difficult sliding applications, it prevents seizing, galling and minimizes friction. Throughout its useful temperature range, there is no oil separation and evaporation. On threaded surfaces, its use will result in break-away torque, a positive measure of its effectiveness.

APPLICATIONS

- Electric switches and components
- Hinges, sliding tracks, and rod guides
- Ways
- Plastic cams

PRODUCT FEATURES

- Organo-clay thickener
- Contains moly and PTFE
- Contains rust and corrosion inhibitors
- Mechanically stable

BENEFITS

- High dropping point for superior retention properties and reduced oil separation
- Reduces friction and wear
- Prevents rust and corrosion protecting components and extending their life
- Will not soften and run out

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

7/25/2022

Typical Physical Properties		
Property	Test Method	2
Worked Penetration	ASTM D217	275
NLGI Grade		2
Thickener Type		Organo-clay
Viscosity @ 40°C, cSt	ASTM D445	96.8
Viscosity @ 100°C, cSt	ASTM D445	10.9
Dropping Point, °C (°F)	ASTM 2265	>260 (>500)
Mechanical Stability, 10000 strokes, %	ASTM D217	7
Lubricating Solids Type		MoS ₂ and PTFE
Useful Temperature Range, °C (°F)		-29 to 260 (-20 to 500)
Color		Black

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

7/25/2022