

PRODUCT DATA SHEET



NO-TOX® FOOD GRADE WATERPROOF CHAIN LUBRICANT

No-Tox Food Grade Waterproof Chain Lubricant, commonly known as No-Tox Waterproof Chain Lube, is a tacky and waterproof chain lubricant and is NSF H1 registered for use where incidental food contact may occur. **No-Tox Food Grade Waterproof Chain Lubricant** is recommended for most unheated chain applications found in the "clean" industries such as food, beverage, pharmaceutical and personal care products. It is fortified with proprietary anti-wear agents and other additives that promote penetration and lubrication of sprockets, links, pins and bushings. **No-Tox Food Grade Waterproof Chain Lubricant** also contains rust and corrosion inhibitors and special polymers to resist flinging and dripping.

Applications

 Widely used in food and poultry plants operating under the Federal Meat and Poultry Products Inspection Program's Food Safety and Inspection Service (FSIS)

Features and Benefits

| * | NSF H1 registered | Use where incidental food contact may occur. |
|----------|-------------------------------|---|
| ♦ | Compliances | Kosher and Pareve approved. Halal certified. |
| • | Bacteriological protection | Effectively inhibits the growth of certain bacteria, yeast and mold in the lubricant. |
| • | Anti-wear protection | Reduces friction and wear. |
| • | Rust and oxidation prevention | Longer service life. |
| • | Tacky and non-drip | Provides superior adhesion to metal. |

General Description

No-Tox Food Grade Waterproof Chain Lubricant is blended to give outstanding anti-wear and rust protection. The convenient aerosol container sprays the unique formulation on the chain protecting against rust and metal-to-metal contact. **No-Tox Food Grade Waterproof Chain Lubricant**, formulated with the highest quality ingredients, meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified. **No-Tox Food Grade Waterproof Chain Lubricant** is available in bulk and spray aerosol forms.

Product No. 301247, 301248

Page 1 of 2 1/2/2018

With continual research and development, Calumet reserves the right to change the information contained herein. The Company is not responsible for misuse or misapplication of its products.

NO-TOX® FOOD GRADE WATERPROOF CHAIN LUBRICANT

TYPICAL PROPERTIES

| Product No. | <u>301247</u> | <u>301248</u> |
|---|---------------|---------------|
| Old Product No. | <u>64060</u> | <u>64070</u> |
| | Bulk | Spray |
| ISO Viscosity Grade | 460 | |
| Viscosity, ASTM D445 | | |
| @ 40°C, cSt | 466 | |
| @ 100°C, cSt | 36.8 | |
| Rust Test, ASTM D665, Procedure A & B | Pass | |
| Falex EP Test, ASTM D3233 Method B Non-seizure Load, lbf | 1250 | |
| Color | Pale Yellow | White Foam |

Aerosol Caution: Use in a well-ventilated space.

Product is flammable and should be used with appropriate caution.

Do not spray on a hot surface or in proximity to flames or open fire.

Do not puncture or incinerate container, even when empty.

Always wear safety glasses when using this product.

Keep container away from heat.

Use in the manufacturing process only. For food plant and other industrial uses. Avoid direct addition to food during use of product. Use as recommended by a company representative. Use with minimum application necessary to accomplish desired technical effect. Remove excess with clean cloth. To be used where contact of the lubricant with food is incidental at a level of the product not to exceed 10 ppm.

Page 2 of 2 1/2/2018