



Saw Guide Oil

Bel-Ray® Saw Guide Oil is designed with premium base stocks and additive system that reduces friction between saw and guide components. They are designed to be used for lubricating arbor bearings and saw guide systems. Bel-Ray Saw Guide Oil contains rust inhibitors and a tackifier to resist slinging.

APPLICATIONS

Recommended as a lubricant for multiple equipment types used in timber industry mills. Saw Guide Oil can be applied by intermittent drip system, brush or spray on:

- Gang edgers
- Trimmers
- Industrial bandmills and circular saws
- Smaller, portable circular or bandsaws
- Arbor bearings

PRODUCT FEATURES

- Excellent rust and oxidation chemistry
- Tackifier enhanced formula
- Improved blade lubricity
- Low pour point

BENEFITS

- Excellent protection from rust and corrosion; displaces water
- Reduced sling-off and controlled stray mist
- Reduced pitch and varnish deposits on blades
- Great low temperature flow and lubricity

Typical Physical Properties			
Property	Test Method	46	100
Density@15°C, g/cm3	ASTM D4052	0.873	0.877
Viscosity @ 40°C, cSt	ASTM D445	48.5	100
Viscosity @ 100°C, cSt	ASTM D445	7.13	11.4
Viscosity Index	ASTM D2270	105	100
Flash Point, °C (°F)	ASTM D92	213 (415)	216 (421)
Pour Point, °C (°F)	ASTM D97	-9 (-16)	-9 (16)

DISTRIBUTED BY:
 Calumet Branded Products, LLC
 2780 Waterfront Pkwy. E. Dr., Suite 200
 Indianapolis, IN 46214
 Technical Services: 317-328-5660
 www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

6/27/2024