

Electric Switch Contact White Grease

Electric Switch Contact White Grease, commonly known as Bel-Ray 63860-A Grease, is a non-melting, anti-seize paste. The exceptional low frictional properties and load carrying abilities of Electric Switch Contact White Grease are derived from its PTFE solid lubricant. Electric Switch Contact White Grease delivers exceptional performance on sliding surfaces and thread applications. Effective over a broad temperature range for the most difficult sliding applications. It contains a high level of PTFE, which helps prevent seizing, galling and minimizes friction. Electric Switch Contact White Grease can be used in exposed areas where its appearance will not detract from an overall impression of a finished part or unit such as an assembled switch. Moreover, its excellent thermal stability resists deterioration in service, permitting long useful life.

APPLICATIONS

- Electric switches and components
- Hinges, sliding tracks, and rod guides
- Ways
- Plastic cams

PRODUCT FEATURES

- Organo-clay thickener
- Contains PTFE
- Contains rust and corrosion inhibitors
- Mechanically stable

BENEFITS

- High dropping point for superior retention properties and reduced oil separation
- Reduces friction and wear
- Prevents rust and corrosion protecting components and extending their life
- Will not soften and run out

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

7/25/2022

Typical Physical Properties		
Property	Test Method	2
Worked Penetration	ASTM D217	284
NLGI Grade		2
Thickener Type		Organo-clay
Viscosity @ 40°C, cSt	ASTM D445	284
Viscosity @ 100°C, cSt	ASTM D445	21.1
Dropping Point, °C (°F)	ASTM 2265	>260 (>500)
Mechanical Stability, 10000 strokes, %	ASTM D217	7
Lubricating Solids Type		PTFE
Useful Temperature Range, °C (°F)		-15 to 260 (5 to 500)
Color		White

DISTRIBUTED BY:

Calumet Branded Products, LLC
 2780 Waterfront Pkwy. E. Dr., Suite 200
 Indianapolis, IN 46214
 Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

7/25/2022