

## Molylube High Temperature Grease

Molylube High Temperature Grease, commonly known as Molylube 65 Grease, is a synthetic based, sodium complex grease recommended for high temperature and heavy load applications. It is formulated with molybdenum disulfide (moly), graphite lubricating solids, extreme pressure and anti-wear additives, and rust and corrosion inhibitors for maximum protection under severe operating conditions. The sodium complex thickener and synthetic base fluids of Molylube High Temperature Grease are virtually residue-free. Molylube High Temperature Grease continues to provide excellent protection as temperatures increase to 149°C (300°F). Molylube High Temperature Grease leaves no undesirable residues when exposure to temperatures in excess of 260°C (500°F), optimizing bearing performance under these conditions.

### APPLICATIONS

- Slides
- Bushings
- Ball bearings
- Pedestal Slides
- Vibrating screens
- Furnace table rolls
- Molten lead pumps
- Refractory kiln car wheels
- Pins
- Valve gear guides
- Roller bearings
- Paw-grip guides
- Conveyor wheels
- Wheel bearings on annealing cars

### PRODUCT FEATURES

- Sodium complex thickener
- Fully synthetic base fluids
- Moly and graphite lubricating solids
- Extreme Pressure and anti-wear properties

### BENEFITS

- High dropping point, high temperature residue free
- Long-life capability
- Reduces friction and provides high temperature lubrication
- Maximizes component useful life helping to reduce replacement part costs and lost production time

#### DISTRIBUTED BY:

Calumet Branded Products, LLC  
2780 Waterfront Pkwy. E. Dr., Suite 200  
Indianapolis, IN 46214  
Technical Services: 317-328-5660  
[www.belray.com](http://www.belray.com)

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

9/19/2023

Typical Physical Properties		
Property	Test Method	1
Worked Penetration	ASTM D217	325
NLGI Grade		1
Thickener Type		Sodium Complex
Viscosity @ 40°C, cSt	ASTM D445	188
Viscosity @ 100°C, cSt	ASTM D445	15.3
Dropping Point, °C (°F)	ASTM 2265	>260 (>500)
Lubricating Solids Type		MoS <sub>2</sub>
4-Ball EP Test, Weld Load, kg	ASTM D2596	500
Corrosion Protection, Federal Method	Method 5322	Pass
Useful Temperature Range, °C (°F)		-18 to 316 (0 to 600)
Color		Dark Grey