

No-Tox Food Grade Chain Lubricant

No-Tox Food Grade Chain Lubricant, commonly known as No-Tox Chain Lubricant 550, is suitable for most chain lubrication requirements found in the “clean” industries such as food, beverage, pharmaceutical and personal care products. No-Tox Food Grade Chain Lubricant coats and penetrates to lubricate the sprockets, links, pins and bushings to reduce friction and wear, and is fortified with rust and corrosion inhibitors for added chain protection. No-Tox Food Grade Chain Lubricant is blend of white mineral oil with performance enhancing additives to give outstanding anti-wear and rust protection. Its unique formulation provides the chain protecting against rust and metal-to-metal contact.



Nonfood Compounds
H1 Registered,
ISO 21469 Certified

No-Tox Food Grade Chain Lubricant, formulated with the highest quality ingredients, meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified. ISO 21469 certified food grade lubricant.

APPLICATIONS

Widely used in food and poultry plants operating under the Federal Meat and Poultry Products Inspection Programs' Food Safety and Inspection Service (FSIS)

PRODUCT FEATURES

- NSF H1 registered and ISO 21469 certified
- Bacteriological protection
- Kosher and Pareve approved
- Halal certified
- Excellent anti-wear performance
- Rust and oxidation stability
- Emulsifies with water

BENEFITS

- Use where incidental food contact may occur
- Effectively inhibits the growth of certain bacteria, yeast, and mold in the lubricant
- Reduces friction and wear
- Protects equipment in wet environments
- Eliminates sticking and clogging in wet environments

Typical Physical Properties

Property	Test Method	100
ISO Viscosity Grade	ISO 3448	100
Specific Gravity @ 60°F	ASTM D1298	0.857
Viscosity @ 40°C, cSt	ASTM D445	110
Viscosity @ 100°C, cSt	ASTM D445	12
Viscosity Index	ASTM D2270	98
Flash Point, °C (°F)	ASTM D92	240 (464)
Pour Point, °C (°F)	ASTM D97	-9 (15)
Fire Point, °C (°F)	ASTM D92	250 (482)
Falex EP Test Non-Seizure Load, lbf	ASTM 3233	1500

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

5/11/2022