

No-Tox Food Grade Extreme Pressure Grease

No-Tox Food Grade Extreme Pressure Grease, commonly known as No-Tox EP Grease, is a white mineral oil based, aluminum complex grease. It is fortified with non-toxic lubricating solids, Extreme Pressure and anti-wear additives, and rust and corrosion inhibitors. No-Tox Food Grade Extreme Pressure Grease is a low friction, waterproof grease that remains in place, protecting components from wear and corrosion.

No-Tox Food Grade Extreme Pressure Grease meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified. ISO 21469 certified food grade lubricant.



Nonfood Compounds
H1 Registered,
ISO 21469 Certified

APPLICATIONS

- Plain and anti-friction bearings
- Lightly loaded gears
- Extreme pressure applications
- Wet and wash-down areas
- Most heavy-duty grease applications in food and beverage plants where extreme pressure performance is required

PRODUCT FEATURES

- NSF H1 registered and ISO 21469 certified
- Bacteriological protection
- Kosher and Pareve approved
- Halal certified
- Extremely waterproof
- Extreme pressure and anti-wear properties

BENEFITS

- Use where incidental food contact may occur
- Effectively inhibits the growth of certain bacteria, yeast, and mold in the lubricant
- Protects machine components subjected to high moisture operating conditions and wash-down procedures
- Maximizes component life helping to reduce replacement part costs and lost production time

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

5/11/2022

TECHNICAL DATA SHEET



Typical Physical Properties		
Property	Test Method	0
Worked Penetration	ASTM D217	370
NLGI Grade		0
Thickener Type		Aluminum Complex
Viscosity @ 40°C, cSt	ASTM D445	106
Viscosity @ 100°C, cSt	ASTM D445	11.6
Dropping Point, °C (°F)	ASTM 2265	240 (464)
Water Washout %	ASTM D1264	3.9
4-Ball EP Test, Weld Load, kg	ASTM D2596	250
Rust Protection	ASTM D1743	Pass
Color		White

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

5/11/2022