

No-Tox Food Grade Silicone Lubricant Spray

No-Tox Food Grade Silicone Lubricant Spray, commonly known as No-Tox Silicone Lube, is a high viscosity, pearlescent, smooth, tacky, and waterproof silicone fluid in an aerosol package. No-Tox Food Grade Silicone Lubricant Spray is compatible with most seal materials. It is resistant to many reactive chemicals that may be encountered in “clean” industries such as food and beverage, pharmaceuticals and personal care plants. No-Tox Food Grade Silicone Lubricant Spray is ideal for use as a general lubricant, cleaner and preservative.



No-Tox Food Grade Silicone Lubricant Spray, formulated with the highest quality ingredients, meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified. ISO 21469 certified food grade lubricant.

Nonfood Compounds
H1 Registered,
ISO 21469 Certified

APPLICATIONS

Widely used in food and poultry plants operating under the Federal Meat and Poultry Products Inspection Program's Food Safety and Inspection Service (FSIS)

PRODUCT FEATURES

- NSF H1 registered and ISO 21469 certified
- Bacteriological protection
- Kosher and Pareve approved
- Halal certified
- Chemically inert
- Chemically resistant
- Waterproof

BENEFITS

- Use where incidental food contact may occur
- Effectively inhibits the growth of certain bacteria, yeast, and mold in the lubricant
- Will not affect rubber, plastic, or metal
- Unaffected by mild acids, alkalis, alcohol, and glycol
- Ideal for wet conditions and water displacing

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

5/11/2022

Typical Physical Properties		
Property	Test Method	
Viscosity @ 25°C, cSt	ISO 3448	425
Viscosity @ 40°C, cSt	ASTM D445	326
Viscosity @ 100°C, cSt	ASTM D445	139.0
Flash Point, °C (°F)	ASTM D92	>321 (>610)
Color		Off-white

Caution: Use in a well-ventilated space. Product is flammable and should be used with appropriate caution. Do not spray on a hot surface or in proximity to flames or open fire. Do not puncture or incinerate container, even when empty. Always wear safety glasses when using this product. Keep container away from heat.

Use in the manufacturing process only. For food plant and other industrial uses. Avoid direct addition to food during use of product. Use as recommended by a company representative. Use with minimum application necessary to accomplish desired technical effect. Remove excess with clean cloth.

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

5/11/2022