

No-Tox Food Grade Seamer Oil

No-Tox Food Grade Seamer Oil, commonly known as No-Tox Seamer Oil E, is a high-performance lubricant with exceptional anti-wear and emulsibility. Its anti-wear and oxidation protection properties increase equipment life and decrease downtime. No-Tox Food Grade Seamer Oil is designed to lubricate and clean components that are exposed to moisture in the form of water, fruit and vegetable juices and soft drinks. No-Tox Food Grade Seamer Oil is recommended for can seaming equipment and similar applications found in “clean” beverage and food processing plants.



No-Tox Food Grade Seamer Oil is formulated with the highest quality USP white mineral oils and food grade additives and meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified. ISO 21469 certified food grade lubricant.

Nonfood Compounds
H1 Registered,
ISO 21469 Certified

APPLICATIONS

- Angelus can seamers
- FMC Rotary Cookers and Sterilizers
- Circulating oil systems where contamination with water or food juice may occur
- Chains involving high humidity conditions

PRODUCT FEATURES

- NSF H1 registered and ISO 21469 certified
- Kosher and Pareve approved
- Halal certified
- Bacteriological protection
- Outstanding anti-wear performance
- Excellent emulsibility

BENEFITS

- Use where incidental food contact may occur
- Effectively inhibits the growth of certain bacteria, yeast, and mold in the lubricant
- Excellent equipment protection while maintaining superior film strength in extreme application conditions
- Adheres to surfaces
- Provides excellent rust protection and reduces equipment maintenance periods and downtime

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

5/11/2022

Typical Physical Properties		
Property	Test Method	150
ISO Viscosity Grade	ISO 3448	150
Viscosity @ 40°C, cSt	ASTM D445	150
Viscosity @ 100°C, cSt	ASTM D445	15.2
Viscosity Index	ASTM D2270	102
Pour Point, °C (°F)	ASTM D97	-9 (15)
Copper Strip Corrosion	ASTM D130	1A
Rust Test	ASTM D665	Pass
4-Ball Wear Scar Diameter, mm	ASTM D4172	0.4
Falex EP Test Non-seizure Load, lbf	ASTM 3233	1250
Color		Water-white

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

5/11/2022