

Semi-Fluid Grease

Semi-Fluid Grease, commonly known as Bel-Ray MA-1500 Heavy, is an adhesive, semi-fluid lubricant, ideal for enclosed gears where poor sealing or leakage is unacceptable. Semi-Fluid Grease is extremely effective in general purpose lubrication of bearings or sliding surfaces where a higher degree of retention is desired. Unlike most gear lubricants, Semi-Fluid Grease will increase in viscosity during use, maximizing retention in hard-to-lubricate bearings and minimizing leakage from gear cases with faulty seals. The Extreme Pressure and anti-corrosion properties of Semi-Fluid Grease will continue to provide the protection needed in the harshest working conditions.

Semi-Fluid Grease is not recommended for circulation systems or where upper bearings depended on splash lubrication. For effective lubrication of upper bearings fill gear cases to halfway up the highest bearing or gear in the case.

APPLICATIONS

- Enclosed gear reducers and drives where surging stress and vibration inevitably produce some degree of leakage
- Anti-friction and journal bearings requiring a greater degree of retention for proper lubrication
- Alternative to heavy greases through an automatic lubrication system where multiple and/or long lube lines prevent proper lubrication
- Sliding surfaces, linkages and sleeves requiring low friction, high load protection

PRODUCT FEATURES

- Control oil leakage
- Excellent retention
- Heat resistant

BENEFITS

- Reduces or stops oil leakage when repairs cannot be immediately performed
- Retains its properties and consistency, extending lubrication cycles and reducing consumption
- Effective general-purpose lubrication to temperatures in excess of 204°C (400°F) without thinning

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

7/29/2022

TECHNICAL DATA SHEET



Typical Physical Properties		
Property	Test Method	000
NLGI Grade		000
Thickener Type		Aluminum Complex
Apparent Viscosity (Brookfield) @ 25°C, cP	ASTM D2196	5500
Viscosity @ 40°C, cSt	ASTM D445	257
Viscosity @ 100°C, cSt	ASTM D445	20.5
Copper Strip Corrosion	ASTM D4048	1B
Falex EP Test, Non-seizure Load, lbf	ASTM D3233	3500
4-Ball EP Test, Weld Load, kg	ASTM D2596	400
Timken EP Test, OK Load, kg (lb)	ASTM D2509	20.4 (45)
Flash Point, °C (°F)	ASTM D92	270 (518)
Color		Medium Brown

DISTRIBUTED BY:

Calumet Branded Products, LLC
2780 Waterfront Pkwy. E. Dr., Suite 200
Indianapolis, IN 46214
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

7/29/2022