

6 in 1®

PRODUCT DESCRIPTION

Bel-Ray® 6 In 1® contains anti-wear additives that provide high film strength to this exceptional penetrating and lubricating fluid. It cleans as it lubricates, protects against rust and corrosion, displaces water and reduces friction. 6 IN 1 will not harm electrical contacts, vinyl, wood or paint.

6 IN 1 is not a solvent but a high-performance lubricant. The exceptional penetrating properties make removal of frozen fasteners and fittings much easier. The special anti-wear additives will protect and lubricate all metal surfaces. It provides superior corrosion protection from moisture and leaves an impervious coating for long lasting protection.



PRODUCT FEATURES

- Superior penetration
- Better lubrication
- Corrosion protection
- User friendly
- Low VOC (Volatile Organic Compounds)

BENEFITS

- Penetrates rust and loosens frozen parts
- NOT just a rust preventive; lubricates as it protects
- Displaces moisture leaving behind a protective barrier film impervious to moisture; protects from rust and corrosion for better and longer component life
- Will not affect plastic or painted surfaces; non-toxic, non-corrosive and non-irritating; easy to use aerosol
- Meets the updated CARB (California Air Resource Board) regs

APPLICATIONS

- Powersports – Automotive – Marine: Levers, Cables, Threads, Instruments, Automatic Chokes, Battery Terminals, Ignition Parts, Wires, Doors, Locks
- Lubrication and rust protection of chains, cables, hinges, locks, lawn equipment, hunting and fishing gear, tools, and more
- For loosening frozen parts, nuts, bolts, etc.
- For displacing moisture and protecting and preserving against corrosion in all environments

DISTRIBUTED BY:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

7/24/2026

TECHNICAL DATA SHEET



PRODUCT DATA

Typical Properties		
Property	Test Method	
Viscosity @ 40°C (cSt)	ASTM D445	6.07
Viscosity @ 100°C (cSt)	ASTM D445	1.99
Flash Point, °C (°F)	ASTM D92	98 (208)

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com

DISTRIBUTED BY:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

7/24/2026