

ATV & SxS 4T Engine Oil SAE 10W-40

PRODUCT DESCRIPTION

Bel-Ray® ATV & SxS 4T engine oil is a premium multi-grade engine oil developed for the unique demands of all 4-stroke ATVs, side-by-side (SxS), Quads, and UTVs. This specially formulated engine oil provides superior protection and lubrication performance for any 4-stroke ATV, air-cooled or liquid-cooled. ATV & SxS 4T is wet clutch compatible and can be used to lubricate transmissions in vehicles that share oil for the engine and transmission. Bel-Ray ATV & SxS 4T engine oil is the best choice for off-road recreational and utility vehicles.



PRODUCT FEATURES

- Bel-Ray's **Rust Defense System (RDS)** additive chemistry
- Exclusive Bel-Ray anti-wear additives
- Low volatility base oils
- Superior detergency and deposit control
- JASO MA2 wet clutch performance

BENEFITS

- Unsurpassed corrosion protection; protects engines from moisture contamination
- Reduced valve train wear, and piston and ring scuffing; promotes greater reliability and equipment life
- Minimized oil consumption for less engine oil top-offs
- Reduced sludge and varnish formation for cleaner and cooler running engines
- Outstanding protection and performance in transmissions that have a wet clutch

APPLICATIONS

- Single- and multi-cylinder, air-cooled and liquid-cooled engines in single passenger and side-by-side ATVs
- Any ATV recommending 10W-40, 15W-40, or 20W-40 4T engine oil
- Store-and-go oil for ATVs during the off-season

DISTRIBUTED BY:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

7/24/2026

TECHNICAL DATA SHEET



PRODUCT DATA

Typical Properties		
Property	Test Method	10W-40
API Service		SM (claimed)
Density @ 15°C (g/mL)	ASTM D4052	0.865
Viscosity @ 40°C (cSt)	ASTM D445	96.8
Viscosity @ 100°C (cSt)	ASTM D445	15.0
Viscosity Index	ASTM D2270	162
Cold Crank Simulator, cP	ASTM D5293	4,527 @ -25°C
Flash Point, °C (°F)	ASTM D92	216 (420)
Pour Point, °C (°F)	ASTM D97	-42 (-44)

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com

DISTRIBUTED BY:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

7/24/2026