



No-Tox[®] Food Grade Clear Grease

PRODUCT DESCRIPTION

Bel-Ray[®] No-Tox[®] Food Grade Clear Grease is a white mineral oil based, aluminum complex thickened food machinery grease. No-Tox Food Grade Clear Grease is a general-purpose grease developed specifically for use in the "clean" industries such as food, beverage, pharmaceutical and personal care products. The excellent water-resistant properties of No-Tox Food Grade Clear Grease make it suitable for the wet environments often encountered in the food and beverage industries.

No-Tox Food Grade Clear Grease is fortified with rust and corrosion inhibitors for added protection in wet conditions. No-Tox Food Grade Clear Grease meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified.



Nonfood Compounds
H1 Registered,
ISO 21469 Certified

PRODUCT FEATURES and BENEFITS

- NSF H1 registered for use where incidental food contact may occur.
- ISO 21469 certified
- Kosher and Pareve approved
- Halal certified
- Bacteriological protection effectively inhibits the growth of certain bacteria, yeast, and mold in the lubricant
- Aluminum Complex thickener
- Excellent water-resistant properties
- Wide temperature range of usage from -20°C to 177°C (-4°F to 350°F)

APPLICATIONS

Bel-Ray No-Tox Food Grade Clear Grease is recommended for most grease applications where a non-extreme pressure, general purpose grease is required. This includes plain and anti-friction bearings, slides, guides, wet and wash-down areas, and other moving parts.

DISTRIBUTED BY:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

4/30/2026



PRODUCT DATA

Typical Properties				
Property	Test Method	NLGI Grade 1	NLGI Grade 1.5	NLGI Grade 2
Thickener Type		Aluminum Complex	Aluminum Complex	Aluminum Complex
Texture		Smooth	Smooth	Smooth
Worked Penetration @ 25°C, 60 strokes (0.1 mm)	ASTM D217	325	300	280
Density @ 15°C (g/mL)	ASTM D4052	0.869	0.869	0.872
Base Fluid Viscosity @ 40°C (cSt)	ASTM D445	104	104	104
Base Fluid Viscosity @ 100°C (cSt)	ASTM D445	11.8	11.8	11.8
Dropping Point, °C (°F)	ASTM D2265	274 (526)	274 (526)	303 (577)
Water Washout @79°C (175°F), % loss	ASTM D1264	4.5	3	2.5
Low Temperature Performance, @ -20°C (-4°F)				
Starting Torque (g·cm)	ASTM D1478	--	--	241
Torque after 1 hour (g·cm)		--	--	22.9
Corrosion Preventive Properties	ASTM D1743	Pass	Pass	Pass
Color		Clear	Clear	Clear

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com

DISTRIBUTED BY:
 Calumet Branded Products, LLC
 1060 N Capitol Ave
 Suite 6-401
 Indianapolis, IN 46204
 Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

4/30/2026