



No-Tox[®] Food Grade Divider Oil

PRODUCT DESCRIPTION

Bel-Ray[®] No-Tox[®] Food Grade Divider Oil is a versatile, general-purpose lubricant that can be used as a knife lubricant, divider oil, rust protector and mold release agent. It is NSF H1 and 3H registered for use in applications where direct food contact and incidental food contact may occur. No-Tox Food Grade Divider Oil is formulated to minimize gum formation, improve adhesion and reduce friction, and it provides excellent water displacement and will not stain surfaces. Its surface film acts as an anti-rust agent.

No-Tox Food Grade Divider Oil, formulated with the highest quality USP white mineral oils, meets NSF H1, 3H and FDA requirements for materials that may have direct or incidental contact with food as defined under Title 21 CFR, 172.878 and 178.3570. It is Kosher and Pareve approved, as well as Halal certified. ISO 21469 certified food grade lubricant.



Nonfood Compounds
H1 Registered,
ISO 21469 Certified

PRODUCT FEATURES

- NSF H1 and 3H registered
- ISO 21469 certified
- Kosher and Pareve approved
- Halal certified
- Transparent, tasteless, odorless, and colorless
- Non-staining
- High demulsibility

BENEFITS

- Use where incidental food contact may occur
- Prevents discoloration in textile applications
- Excellent water separability

APPLICATIONS

- General purpose, colorless oil for non-extreme pressure and non-anti-wear applications
- Knife lubricants, meat grinders, food mixers, hook lubricants, textile plants
- Rust preventative, release agents, mold process aids

DISTRIBUTED BY:
Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

6/12/2026

PRODUCT DATA

Typical Properties				
Property	Test Method	ISO 15	ISO 32	ISO 68
Density @ 15°C (g/mL)	ASTM D4052	0.852	0.865	0.870
Viscosity @ 40°C (cSt)	ASTM D445	16.0	35.2	68.4
Viscosity @ 100°C (cSt)	ASTM D445	3.70	5.70	8.75
Viscosity Index	ASTM D2270	119	100	99
Pour Point, °C (°F)	ASTM D97	-18 (0)	-18 (0)	-15 (5)
Color		Water-white	Water-white	Water-white

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com