



No-Tox[®] Food Grade Waterproof Chain Lubricant

PRODUCT DESCRIPTION

Bel-Ray[®] No-Tox[®] Food Grade Waterproof Chain Lubricant is a tacky and waterproof chain lubricant. No-Tox Food Grade Waterproof Chain Lubricant is recommended for most unheated chain applications found in the “clean” industries such as food, beverage, pharmaceutical and personal care products. It is fortified with proprietary anti-wear agents and other additives that promote penetration and lubrication of sprockets, links, pins and bushings. No-Tox Food Grade Waterproof Chain Lubricant also contains rust and corrosion inhibitors and special polymers to resist flinging and dripping.

No-Tox Food Grade Waterproof Chain Lubricant, formulated with the highest quality ingredients, meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR 178.3570. It is Kosher and Pareve approved, Halal certified, and ISO 21469 certified. No-Tox Food Grade Waterproof Chain Lubricant is available in bulk and spray aerosol forms.



Nonfood Compounds
H1 Registered,
ISO 21469 Certified

PRODUCT FEATURES and BENEFITS

- NSF H1 registered and ISO 21469 certified
- Kosher and Pareve approved
- Halal certified
- Bacteriological protection effectively inhibits the growth of certain bacteria, yeast, and mold in the lubricant.
- Excellent penetration properties that creep and penetrate deeply into any metal parts
- Tacky formulation provides superior adhesion to metal
- Superior rust and corrosion prevention

APPLICATIONS

Bel-Ray No-Tox Food Grade Waterproof Chain Lubricant is recommended for use in food and poultry plants operating under the Federal Meat and Poultry Products Inspection Program’s Food Safety and Inspection Service (FSIS)

DISTRIBUTED BY:
Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

6/23/2026



PRODUCT DATA

| Typical Properties | | | |
|---|--------------|-------------|-----------------|
| Property | Test Method | Bulk | Spray (Aerosol) |
| ISO Viscosity Grade | | 460 | -- |
| Base Fluid Viscosity @ 40°C (cSt) | ASTM D445 | 460 | 460 |
| Base Fluid Viscosity @ 100°C (cSt) | ASTM D445 | 36.8 | 36.8 |
| Rust Prevention | ASTM D665A&B | Pass | Pass |
| Falex Pin & Vee Block Test Method B, non seizure load (lbf) | ASTM D3233 | 1250 | 1250 |
| Color | | Pale Yellow | Pale Yellow |

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com

DISTRIBUTED BY:
 Calumet Branded Products, LLC
 1060 N Capitol Ave
 Suite 6-401
 Indianapolis, IN 46204
 Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

6/23/2026