

Synthetic Gear Oil

PRODUCT DESCRIPTION

Bel-Ray® Synthetic Gear Oil, an enclosed Extreme Pressure (EP) gear lubricant, is a full synthetic hydrocarbon and ester formulation. It offers outstanding Extreme Pressure and anti-wear properties, as well as excellent viscosity-temperature properties, and extremely low coefficients of friction and traction. Bel-Ray Synthetic Gear Oil is compatible with mineral oils.

PRODUCT FEATURES and BENEFITS

- Premium synthetic base fluids (Polyalphaolefin [PAO] and esters) provide enhanced lubricity, that reduces friction, heat generation, and parasitic loss.
- Superior Extreme Pressure and anti-wear properties greatly reduce wear and gear tooth damage due to extreme pressure boundary lubrication conditions
- Exceptional FZG micropitting test results prevent low-cycle tooth surface damage (micropitting or gray staining) that can lead to catastrophic gear damage.
- Highly filterable that allows easy removal of particulates from the lubricant, promoting less abrasive wear and longer component life.
- Excellent low temperature performance and flow, ideal for cold environments.

APPLICATIONS

Recommended as a lubricant and sealant for slick lines, and braided wirelines and cables.

- Dragline, shovel and heavy process gear cases
- Planetary gear transmissions
- Electric wheel motors
- Compliances: U.S. Steel 224, AGMA 9005-E02, DIN 51517 Part 3

ISO Viscosity Grade	220	320	460	680	1000
Bosch Rexroth	X	X	X		
Caterpillar (Bucyrus)	X	X	X		X
General Electric				X	
LeTourneau			X		
Liebherr		X		X	
Siemens (Flender)	X	X	X	X	

DISTRIBUTED BY:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

7/17/2026

TECHNICAL DATA SHEET



PRODUCT DATA

Typical Properties						
Property	Test Method	220	320	460	680	1000
AGMA Number		5	6	7	8	8A
ISO Viscosity Grade		220	320	460	680	1000
Viscosity @ 40°C (cSt)	ASTM D445	219	317	468	692	927
Viscosity @ 100°C (cSt)	ASTM D445	27.7	36.8	49.5	67.1	99.2
Viscosity Index	ASTM D2270	163	165	167	170	201
Pour Point, °C (°F)	ASTM D97	-48 (-54)	-46 (-51)	-48 (-54)	-42 (-44)	-37 (-35)
Copper Corrosion, 3 h @ 100°C (Rating)	ASTM D130	1b	1b	1b	1b	1b
Rust Prevention	ASTM D665A&B	Pass	Pass	Pass	Pass	Pass
4-Ball Wear Test, @ 1200 rpm, 40 kgf, 60 min, 75°C Scar Diameter (mm)	ASTM D4172	0.30	0.31	0.33	0.31	0.32
Timken EP Test, OK Load, kg (lbs)	ASTM D2782	45.4 (100)	45.4 (100)	45.4 (100)	45.4 (100)	45.4 (100)
FZG Micropitting Test, Fail Stage Endurance Test, GFT-Class	FVA 54	10 High	>10 High	>10 High	>10 High	N/A
FZG Scuffing Load Test, A/16.6/90 and A/8.3/90 Fail Stage	DIN 51534	>14	>14	>14	>14	N/A
Bearing Wear, FAG FE8 Weight Loss, Roller (mg) Weight Loss, Cage (mg)	DIN 51819-3	4 28.5	4 28.5	4 28.5	4 28.5	N/A
Color		Yellow	Yellow	Yellow	Yellow	Yellow

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com

DISTRIBUTED BY:
Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

7/17/2026